

OFFER TO PURCHASE



Date: 01/09/2025
Deal: 25207
Branch: 110
Department: New Sales
Salesperson: Doug Evans

Customer: Division of Transportation
180 N County Farm Rd
Wheaton, IL 60187

Dealer: CIT Trucks, LLC. - Wood Dale
305 W. Northtown Rd.
Suite A
Normal, IL 61761

+SOLD UNITS(s)

	Price:	\$172,432.00
Year: 2026		
Make: Kenworth	Model: T880	

ADDITIONAL UNIT CHARGES

Title Fee

Price: \$165.00

ADDITIONAL UNIT CHARGES

Document Fee

Price: \$295.00

ADDITIONAL UNIT CHARGES

License Plate Fees

Price: \$8.00

ADDITIONAL UNIT CHARGES

Accessories - New KW T800 - FET Exempt

Price: \$14,112.00

Unit Price: \$187,012.00

Subtotal: \$187,012.00

Difference: \$187,012.00

\$0.00

\$0.00

\$0.00

Net: **\$187,012.00**

Balance Due: \$187,012.00

Unit will not be slotted till a Allison 4000 transmission is allocated to this order

Pricing used Sourcewell Contract 032824-KTC

General Manager Printed Name

Purchaser Printed Name

General Manager Signature

Purchaser Signature



Doug Evans
Cell Phone:
Office Phone: 815-639-2000
Email: devans@cittrucks.com

Division of Transportation
180 N. County Farm RD
WHEATON, Illinois 60189
United States of America

William Bell

Vehicle Summary

Unit		Chassis	
Model:	T880 Series Conventional	Fr Axle Load (lbs):	14600
Type:	TRACTOR	Rr Axle Load (lbs):	40000
Description 1:	Highway DC	G.C.W. (lbs):	80000
Description 2:	Clone of Chassis 131045 T880 Series Conventional		
Application		Road Conditions:	
Intended Serv.:	Local Pickup & Delivery: Vehicles which	Class A (Highway)	81
Commodity:	Heavy Machinery	Class B (Hwy/Mtn)	19
Body		Class C (Off-Hwy)	0
Type:		Class D (Off-Road)	0
Length (ft):	0	Maximum Grade:	6
Height (ft):	0	Wheelbase (in):	188
Max Laden Weight (lbs):	0	Overhang (in):	57
Trailer		Fr Axle to BOC (in):	74
No. of Trailer Axles:	2	Cab to Axle (in):	114
Type:	Lowboy	Cab to EOF (in):	171
Length (ft):	35	Overall Comb. Length (in):	620.5
Height (ft):	3	Special Req.	
Kingpin Inset (in):	36	U.S. Domestic Registry, 50-state.	
Corner Radius (in):	6		
Restrictions			
Length (ft):	75		
Width (in):	102		
Height (ft):	13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.

Sales Code	Std/ Opt	Description	Weight
Model			
0000810	S	T880 Series Conventional	15,549
0070060	S	T880	0
0080101	O	CARB Low NOX Omnibus Registration Guidelines Dealer/Customer acknowledges that this vehicle is NOT intended for registration or domicile/primary use in the State of California.	0
0080310	O	EPA Clean Idle Label - Cummins Engines	0
0090000	S	Non-Sleeper w/ Rear Axle Capacity less than 59K.	0
0098413	O	State of Registry: Illinois	0
Engine & Equipment			
0130349	O	Cummins X15 450V 450@1900 1650@900, 2024 with Inte Brake, Productivity Series N09420 C333 0.....Reserve Speed Limit Offset (N09380 C334 0.....Maximum Cycle Distance (C334 N09360 C400 252...Reserve Speed Function Reset N09200 C399 100...Standard Maximum Speed Limit N09400 C401 10...Maximum Active Distance (C40 N09220 C402 0.....Expiration Distance (C402) N09540 C395 0.....Expiration Distance (C395) N09260 C121 70...Maximum Accelerator Pedal Ve N09440 C234 NO....Engine Protection Shutdown (N09460 C231 NO....Gear Down Protection (C231) N09580 C133 5.....Timer Setting (C133) N09680 C233 NO....Idle Shutdown Manual Overrul N09480 C132 1400..Max PTO Speed (C132) N09300 C128 70...Maximum Cruise Speed (C128) N09500 C239 NO....Cruise Control Auto Resume (N09520 C238 NO....Auto Engine Brake in Cruise N09240 C209 100...Hard Maximum Speed Limit (C2 N09780 C190 80...High Ambient Temperature Thr N09740 C188 40...Low Ambient Temperature Thre N09760 C189 60...Intermediate Ambient Tempera N09720 C382 YES...Enable Hot Ambient Automatic N09600 C396 YES...Enable Impending Shutdown Wa N09620 C397 60...Timer For Impending Shutdown N09640 C206 35...Engine Load Threshold (C206) N09560 C225 YES...Enable Idle Shutdown Park Br	470
1000046	O	EPA Emissions Warranty Engine	0
1000151	S	PremierSpec	0
1000243	O	Gearing Analysis: Performance power before economy results.	0

Price Level: January 1, 2024

100% Complete

Date: January 02, 2025

Deal: Highway DC

Quote Number: QUO-1073684-P5R8M6

Printed On: 1/8/2025 12:45:33 PM

Sales Code	Std/ Opt	Description	Weight
1000257	O	Customer's Typical Operating Spd: 70 MPH	0
1000525		RegistrationYear Year of Registration: 2025	0
1000683	O	Effective VSL Setting 65.0 MPH or Greater (USA)	0
1000858	O	Engine Idle Shutdown Timer Disabled	0
1000891	O	Eff EIST NA Expiration Miles Use only with MX and Cummins engines	0
1002080	O	Air Compressor: Cummins 18.7 CFM, Naturally Aspirated for Cummins X15 and X15N engines	0
1051200	S	Air Cleaner: Composite Firewall Mounted PACCAR or Cummins Engines	0
1105220	O	Fan Hub: Horton 2-Speed for X15/X15N	0
1123555	S	Cooling module: 1330 square inches. Includes aluminum radiator core, aluminum charge air cooler, translucent surge tank and washer bottle, silicone hoses, and extended life coolant.	0
1160208	O	Bug Screen: Between Hood & Grille	2
1247263	S	EXH: Single Can 2024 RH Under with RH Side-of-Cab Vertical Tailpipe	0
1290130	O	Tailpipe: 5 in. single 30 in. 45 degree curved.	-1
1321125	O	Fuel Filter:Davco 382 Fuel/Water Separator	8
1321220	O	Run Aid:Cummins TRV for Davco only *For Fuel Filter, X15 AND 2.1 m models	2
1321305	S	Start Aid:12V Heat *For Fuel Filter	0
1504005	O	Immersion Block Heater 120V 1500W W/ Plug Under Door on C500, T660, T800 & W900.	2
1812163	S	Alternator: PACCAR HDS 160 AMP Brushed	0
1821210	S	Batteries: 3 PACCAR GP31 Threaded Post (700-730) 2100-2190 CCA dual purpose.	0
1832039	O	Starter: Delco 39MT w/over crank protection 12 volt	0
1840065	S	12V Low Voltage Disconnect for Battery Protection	0
1900996	O	Jump Start Terminals Under Hood.	12
1901017	S	Remote PTO/Throttle, 12-Pin, Engine Bay Remote Control Provision	0
Transmission & Clutch			
2016612	O	Transmission: Allison 4000RDS 6-speed, With PTO	478

Price Level: January 1, 2024

100% Complete

Date: January 02, 2025

Deal: Highway DC

Quote Number: QUO-1073684-P5R8M6

Printed On: 1/8/2025 12:45:33 PM

Sales Code	Std/ Opt	Description	Weight
		drive gear. No retarder. 6th Generation controls. For vocational applications. Includes shift control, transmission oil temperature gauge, oil level sensor & heat exchanger. Transynd transmission fluid is standard on all Allison 1000, 2000, 3000 & 4000 series transmissions.	
2406453	O	Driveline: 2 Dana SPL250XL 1 Centerbearing Low maintenance offering from Spicer. On-highway 350K mi first service interval, 100K mi subsequent service interval on U-joint, splines lubed for life, quick disconnect end caps.	83
2410018	O	Torque Converter Included W/ Allison Transmission.	0
2410151	O	Pushbutton Control Center Console Mounted. Class 8 with Allison Transmission.	0
2410204	O	Allison Fuel Sense: Delete	0
2410310	O	Allison Neutral at Stop	0
2429378	O	Customer Installed Transmission PTO in the LH Mounted position (8 o'clock) for Allison 3000 & 4000 transmissions.	0
Front Axle & Equipment			
2513030	O	Meritor MFS14 Plus 14.6K 3.74in. Drop Wide Track.	-141
2647009	O	Front Air Disc Brakes: 14.6K Meritor EX+L Optimized RSD reduced stopping distance tractor only.	0
2690028	O	Integral Knuckle for Air Disc Brake, for use on Meritor MFS PLUS Steer Axle	0
2690042	O	U-Shaped Rotor for Meritor Air Disc Brakes.	0
2702500	O	Front Hub: Iron Hub Pilot 14,600 lbs. 11-1/4 in. bolt circle. For use w/ air disc brakes. Consider wheelguards (5850002) w/ aluminum wheels.	48
2741970	S	ConMet PreSet Plus Hub Package; Front Axle.	0
2750001	S	Hubcap: Front Vented.	0
2769000	S	Slack Adjusters Included W/ Front Axle or Brakes. Also use with disc brakes.	0
2864116	O	Front Springs: Taperleaf 16K W/ Shock Absorbers w/ maintenance-free elastomer spring pin bushings. Two leaf. Standard with rubber pins. Not available on W900L.	-85
2895101	O	Single Power Steering Gear: 16K Sheppard SD110.	-64
2899336	S	Power Steering Cooler: Radiator Mounted Air-to-Oil	0
Rear Axle & Equipment			
3122246	O	Dual Meritor MT40-14X3 Hypoid DualTrac Rear Axle rated at 40K. Tandem rear axles.	-419
3200433	O	Rear Axle Ratio - 4.33.	0

Sales Code	Std/ Opt	Description	Weight
3354050	O	Rear Brakes, Meritor Q+ RSD-Compliant S-Cam 16.5x7 in.tandem axle drum brake, Max GAWR 50K.	-24
3392005	O	Dual Rear Brake Drums: Cast. For use with 16.5X7" or 16.5X8.625" brake.	208
3407050	S	Dual Rear Hubs: Aluminum Hub Pilot 46K; 11.25" bolt circle. Requires "R" series outer ends.	0
3441972	S	ConMet PreSet Plus Hub Package; Dual Rear Axle.	0
3465002	O	Tandem Rear Axle Automatic Slack Adjusters. For use with drum brakes.	0
3485207	O	Spring Brake: 3030 Long Stroke Dual 30 Square inches travel. For drum brakes. Helps keep brakes in adjustment longer.	88
3495225	O	FMVSS-136 Stability Control Schedule Review Chassis meets FMVSS-136 requirements and must be equipped with Electronic Stability Control. Reference Option code placed on order.	0
3495231	O	Bendix 6S/6M Anti-Lock Brake System W/ Air traction control (ATC) and electronic stability program (ESP) for tractor.	15
3500057	O	Interaxle Driveline: 1 Dana SPL170XL Tandem Rear Axles Only	-2
3740130	S	Rear suspension: Tandem Kenworth Airglide 460 46K 54 in. axle spacing. 10.5 in. ride height. Includes air suspension dump valve.	0
3830152	S	Air Springs: Heavy-Duty for Airglide 460. Replaces standard duty air springs.	0
Tires & Wheels			
4080220	O	Front tires: Continental HSR3 12R22.5 16PR	-86
4280057	O	Rear tires: Continental HDR2+ 11R22.5 14PR	176
4900008	O	Rear Tire Quantity: 8	0
5043550	O	Front Wheel: Alcoa ULA18 22.5x8.25 MagnaForce aluminum alloy, hub-pilot mount. 7400lb maximum rating. Air Disc Brake compatible. High polish.	-159
5243550	O	Rear Wheel: Alcoa ULA18 22.5x8.25 MagnaForce aluminum alloy, hub-pilot mount. 7400lb maximum rating. Air Disc Brake compatible. High polish.	-316
5900008	O	Rear Wheel/Rim Quantity: 8	0
Frame & Equipment			
6056200	S	Frame Rails: 10-3/4 x 3-1/2 x 3/8in. Steel to 284 in. Truck frame weight is 3.48 lb.-in. per pair of rails. Section modulus is 17.80, RBM is 2,132,000 in.-lbs per rail. Frame rail availability may be restricted based upon application, axle/suspension capacity, fifth wheel setting, or component/dimensional specifications. The results of the engineering review may result in a change to the requested frame rail. If a change is required Kenworth Application	229

Sales Code	Std/ Opt	Description	Weight
		Engineering will advise the dealer of the appropriate material specification for a substitute rail.	
6302460	O	Bumper: Tapered Painted Steel Channel. Requires a bumper setting code.	44
6319485	S	48.5 in. Bumper Setting. Requires a Bumper Code.	0
6321005	O	Removable Front Tow Hooks: 2.	15
6390103	O	Front Mudflaps.	0
6405048	S	Battery Box Module: Short Length Aluminum parallel under cab, aluminum diamond plate cover w/ step. Up to 2 air tanks may mount to bottom of box. Batteries will be oriented perpendicular on rail.	0
6409901	S	Battery Box Location: LH Side.	0
6410010	O	Frame Access Grabhandle(s) LH Mounted. Placement and quantity of grabhandles may vary due to FMCSR frame access requirements.	2
6410011	O	Frame Access Grabhandle(s) RH Mounted. Placement and quantity of grabhandles may vary due to FMCSR frame access requirements.	2
6410092	O	Frame Access Grabhandle Horizontal Mounted at midpoint of sleeper or Daycab.	2
6414010	O	Deckplate: full coverage, as much as possible keeping ahead of fifth wheel angle or 10 feet maximum.	42
6417009	O	Frame Access Steps: 2 for Fuel/Hydraulic Tank BOC, RH mount. Available when rear of tank under extends more than 14 in. behind rear of cab, sleeper, or side extender. For tanks located totally behind a cab or sleeper the front of the tank must be within 14 in. from the rear of cab, sleeper, or side extender.	6
6451090	S	C5, T6, T8 Non-Polished DPF/SCR or CNG Cover diamond plate w/ step. For use w/ 2010 or later exhaust systems. For T8, use extended length non-polished battery box on opposite rail to match the length of under cab components. End plates will be painted standard black frame color.	0
6543612	O	Fifth Wheel: ILS No-Tilt Air, HoI FW35N930YL00 30 in. slide, 9.00 in. height. No-tilt convertible w/ outboard mounting angles, 55K vertical rating, LH release. Air slide control valve standard in dash. Accommodates a 2 in. SAE kingpin. Requires some style of trailer connections.	605
6679914	O	Any Changes to Rear Cab/Sleeper Area Must Comply w/FMCSR 399.	0
6679915	O	Customer-Installed Bulkhead and/or Headache rack.	0
6680000		FifthWheelSetting FW rear/fixed setting ahd of bogie 0 in indicates rearmost setting measured forward from centerline of tandem or single rear axle	0
6721102	S	Rear Mudflap Arms: Betts B-25 Standard-Duty, straight. Includes B1732 mounting brackets as standard.	0

Sales Code	Std/ Opt	Description	Weight
6722000	S	Rear Mudflap Shields: White Plastic Antisail W/ Kenworth logo.	0
6738107	O	Quarter Fenders: Brackets Painted Steel For customer-installed fenders.	11
6744002	O	Long Tractor Taper Top Flange Bent & Welded W/ crossmember. Taper is 4in. longer than standard. Non-towing end-of-frame configuration.	17
6747000	O	Shortest End-of-Frame Cutoff With Specified end-of-frame configuration. Selecting this code will override the overhang dimension found in the Vocational Analysis of the sales tool.	0

Fuel Tanks & Equip

7214075	O	Fuel Tank: 75 US Gallon 24.5 in. Aluminum BOC replace. Class 8 fuel tanks w/ o locking caps include an anti-siphon device on the filler neck.	-11
7721060	O	Hydraulic Tank: 60 US Gallon 24.5 in. Aluminum add.	94
7722156	O	Medium Aerodynamic Round DEF Tank, 21 Gallons. The tank will be located just rearward of the under cab component on the side you specified. Standard capacity is calculated by fuel capacity of the vehicle and will accommodate two diesel fill-ups for every DEF fill-up. For 1:1 DEF fuel fill ratio, add 7889204.	31
7889208	O	DEF to fuel fill ratio between 1.25:1 and 2:1.	0
7889220	O	DEF Tank Steps	27
7889245	S	Anti-Siphon Device in Fuel Tank Filler Neck. For any number of fuel tanks.	0
7889604	S	DEF Tank Location is LH.	0
7889803	O	Hydraulic Tank Location Right Side Behind Cab.	0
7889811	O	2 Hydraulic Tank Fittings, Rear Top, Bottom.	0
7940075	O	Location: 75 gal fuel tank LH behind cab	0

Cab & Equipment

8025301	S	Cab: Stamped Aluminum Cab with Panoramic Curved glass windshield. Standard with stamped aluminum doors, heavy duty in-swinging hinges, and triple sealed doors. Manufactured using self-piercing rivets and structural adhesive. Includes LED exterior marker lights and turn signals.	0
8090604	O	Hood: T880 Set-Back Medium Length. 122.6 inch BBC W/Std Bumper.	15
8108011	S	Cab HVAC - Day Cab and 40 in. Sleeper System With Defrost, A/C, and 48,000 BTU/hr Heater. Includes automatic temperature control with one touch defrost operation and dash mounted cab temperature and solar intensity sensors. Pleated fresh air filter and cabin recirculation air filter standard. The Kenworth HVAC system is designed to provide optimal heating and cooling in all	0

Price Level: January 1, 2024

100% Complete

Date: January 02, 2025

Deal: Highway DC

Quote Number: QUO-1073684-P5R8M6

Printed On: 1/8/2025 12:45:33 PM

Sales Code	Std/ Opt	Description	Weight
		operating environments without need for additional insulation. Cab HVAC without sleeper heater AC is available with 40in sleeper.	
8201047	S	Kenworth Smartwheel: 18 in. Non-Leather With Integrated Radio and Cruise Controls.	0
8201051	O	Column Mtd Retarder Control, RH Side Use with Manual & Allison Transmissions Only.	0
8201200	S	Adjustable Telescoping Tilt Steering Column.	0
8203060	O	5 Sets of Keys. Replaces Standard 2 Sets of Keys.	0
8203196	O	Dash Mounted Compact Trailer Brake Valve. Self Returning.	0
8205087	O	Auto Suspension Dump W/PTO Engagement Interlock. This feature automatically dumps air from the truck suspension when any PTO is engaged. The intent of this feature is to deflate the air suspension air bags while the load is raised to help alleviate any imbalance or instability that can occur with the air bags inflated.	2
8205135	O	Information for Customer-Installed PTO Muncie 10-bolt.	0
8205177	O	Dash Switch:1st Allison-Mounted PTO. Electric switch and wiring are factory-installed to control the 1st Allison Trans mounted PTO.	0
8208497	O	Four Spare Switches: Wired to Power.	0
8221144	O	Gauge: Air Suspension Pressure Gauge.	0
8222404	S	Gauge: DD Virtual Gauge - Oil Temp Engine	0
8222413	S	Gauge: DD Virtual Gauge - Manifold Pressure Boost	0
8222414	S	Gauge: DD Virtual Gauge - Engine Percent Torque	0
8282027	S	Main Instrument Package: 15" Digital Display. Includes Speedometer, Tachometer, Primary Air Pressure, Secondary Air Pressure, Fuel Level #1, DEF Level, DPF Filter Status, Fuel Economy, Oil Pressure, Coolant Temp, OAT and Voltmeter, and Air Application.	0
8282108	O	Modular Dash Options: RH Dash Storage Unit With two shelves. Reduces total gauge count; HD by 6 and MD by 4.	0
8282120	O	USB Charging Port - Dash Panel *Requires 15" Digital Display 8282027/8282028	0
8300008	S	Interior Color: Slate Gray	0
8330102	S	Interior Package: Vantage Daycab Includes durable headliner and vinyl sidewalls with geometric patterned trim and anodized aluminum accents throughout. Convenient overhead storage cubbies, full size glove box, two center console cupholders, and large door pad map pocket. Standard LH/RH power windows, electric	0

Sales Code	Std/ Opt	Description	Weight
		door locks, interior LED lighting, nighttime-friendly red ambient lighting for dash and footwell, and door mounted courtesy light. Includes two standard 12V power outlets. Driver sunvisor includes strap.	
8390634	S	Rubber Floormat	0
8410200	O	Driver Seat: GT701 HB with Vinyl material. The GT701 is standard with a single air bag, scissor linkage seat suspension. It includes a single chamber lumbar support, 10in Fore/Aft adjustment, 7in Up/Down adjustment, 2.5in pan extension, 51 degree seat back recline, and 16 degree full seat tilt. Includes 3-point matching seat belts. DR seat standard w/ dual armrests.	0
8460199	O	Rider Seat: GT701 IB with Vinyl material. The GT701 is standard with a single air bag, scissor linkage seat suspension. It includes a single chamber lumbar support, 10in Fore/Aft adjustment, 7in Up/Down adjustment, 2.5in pan extension, 51 degree seat back recline, and 16 degree full seat tilt. Includes 3-point matching seat belts. RD seat standard w/ LH armrest.	34
8490181	S	Seat Color: Black	0
8601431	O	Kenworth Radio DEA710 AM/FM/WB/USB, Phone Bluetooth Disabled	0
8698974	S	Base Level Audio System - Daycab:High Performance Door Speakers.	0
8699926	O	CB Installation Kit: Center Mounted of Header. W/header mounted quick release CB mount. One red power post & one black ground post. Includes dual antenna leads located on the mirror brackets. Includes dual antenna & separate speaker.	2
8700196	O	Turn Signal: Self-Cancelling	0
8700283	S	LH and RH Trip Ledge Rain Deflectors	0
8700601	S	Global Telematics Unit	0
8800372	O	Grabhandle: LH, Exterior, Side of Cab - Ergonomic Grab Handle Mounted To The Left Hand Exterior Of The Cab For Entry and Exit.	3
8800402	S	Dual Cab Interior Grabhandles: A Pillar Mounted Dash Wrap and B Pillar Mounted Grabhandles	0
8832113	S	Kenworth Daylite Door With Standard LH/RH electric door locks and LH/RH electric window controls.	0
8841411	S	Single Air Horn Under Cab.	0
8850139	S	Look-Down, Pass. Door, Black 11x6	0
8850828	O	Mirror: RH Hood Mounted, Rectangle 8x6, Chrome	4
8850829	O	Mirror: LH Hood Mounted, Rectangle 8x6, Chrome	4
8865002	S	Aero Mirror: Dual Kenworth Aerodynamic Motorized	0

Sales Code	Std/ Opt	Description	Weight
		heated mirrors, 7in X 13in with cab color mirror shell and black mirror arms. Also includes LH/RH heated 6in X 7in convex mirrors. Mirror brackets set for 8-1/2 ft load width. Mirror controls located on driver side door pad.	
8871446	S	Rear Cab Stationary Window 19in x 36in	0
8890101	S	One-Piece Bonded-In Windshield With Curved Glass. Standard.	0
8890135	S	Exterior Stainless Steel Sunvisor.	19
8890300	O	Fender Close-Out: Below Headlamp, Behind bumper. *NOT available with 3-piece bumper.	0
8890359	O	Delete Wheelwell Fender Extension	-4
8890876	S	Kenworth Cab/Sleeper Air Suspension.	0
Lights & Instruments			
9010553	S	Headlamps: SAE Dual Halogen Complex Reflector	0
9022137	S	Marker Lights: Five Rectangular LED.	0
9030016	S	Turn Signal Lights: Flush Mounted LED. Mounted at top of fender wheel arc.	0
9030052	S	LED Stop, Turn, Tail: With Two LED Backup Lights and With An LED License Plate.	0
9058071	O	Switch, Wiring, and Indicator Light for Customer Installed Floodlights. 1st Set. Pigtail Routed Through Pass Thru Grommet. 10ft Jumper Harness Shipped Loose.	1
9059901	O	Floodlight Location: Located High - First Set. This Code To Be Used With Flush-Mount (9052011) or C/I (9058071) Codes Only.	0
9080148	O	Dual Low-Profile Brackets, Switch & Wiring centered over door of cab for C/I beacon lamp.	4
9090039	S	Marker Lights: Interrupter Switch. Included in Turn Signal For All Models Except T3. The T3 Switch Is In The Dash.	0
9090049	S	Omit Brake Light with Engine Brake. Can only be selected when chassis also has engine brake. Cannot be used with options to delete engine brake.	0
9090126	O	Electric Backup Alarm: Meets SAE J994 & OSHA requirements.	4
9090849	O	Polyswitches Replacing Fuses. Switch Will automatically reset after removal of excess load.	0
Air Equipment			
9101219	O	Air Dryer: Bendix AD-HF Extended Purge Heated With Puraguard	0
9108001	S	Moisture Ejection Valve W/ Pull Cable Drain.	0

Sales Code	Std/ Opt	Description	Weight
9110100	O	Tractor Kit: Slide Bar, Spring Hanger & Composite gladhand/light plug holder mounted on back of cab/sleeper. Air and light line connections located on outboard style LH frame mounted bracket. Kit includes dash mounted trailer air supply valve, trailer hand control valve, and hoses/fittings for the valves. Dash mounted parking brake valve and tractor protection valve are standard. Air lines are detachable at one end only, light lines are detachable at both ends. Conspicuity components are standard.	0
9120012	O	Air and light line length 12 feet	0
9140020	S	Nylon Air Tubing in Frame & Cab, Excluding Hoses subject to excessive heat or flexing.	0
9140328	O	Trailer ABS Electric Supply Through SAE J560 7-pin connector per TMC RP137).	0
9140535	O	12' PACCAR Premium Spiral Wrap & SS Clamp With 12' Phillips QCP Light Line. Requires 12' air/light line code.	0
9140701	O	Optional Hosetenna Bracket Location 1ft BOC/sleeper. Hosetenna bracket will be located plus or minus six inches from any non-standard location requested	0
Extended Warranty			
9200021	S	Base Warranty - Standard Service Heavy Duty 12 months / 100,000 miles / 160,000 km.	0
9210401	O	Allison 4000 Series Transmission Surcharge	0
9212653	O	TruckTech+ RD - 5YR Sub Cummins Engines	0
9220001	O	Base Warranty: Emissions 5YR/100K MI - EPA Engine	0
Miscellaneous			
9409852	O	GHG Secondary Manufacturer: Does Not Apply	0
9490206	O	Warning Triangle Reflector Kit: Shipped Loose. Kit consists of 3 triangles in plastic carrying case. Not floor mounted.	4
9490404	O	One 5 lb. Dry Chemical Type Fire Extinguisher mounted outboard of driver seat. Class ABC.	11
9491652	S	EMUX Architecture	0
Promotions			
Paint			
9700000	O	Paint Color Number(s).	0
		N9702 A - L0662 SCHOOL BUS YELLOW N9770 BUMPER N0001 BLACK N9720 FRAME N0001 BLACK	
9943014	O	Steel Bumper Painted Frame Color	0

Price Level: January 1, 2024

100% Complete

Date: January 02, 2025

Deal: Highway DC

Quote Number: QUO-1073684-P5R8M6

Printed On: 1/8/2025 12:45:33 PM



Sales Code	Std/ Opt	Description	Weight
9943051	O	Day Cab Premium Paint	0
9944820	S	1 - Color Paint - Day Cab Color will be White if no other color is specified.	0
9960003	O	Non-Standard Paint Color.	0
9965510	S	Base Coat/ Clear Coat. The Kenworth Color Selector contains additional instructions, as well as information on Kenworth paint guidelines and surface finish applications. Kenworth is standard with Dupont Imron Elite paint.	0

Special Requirements

Special Requirement 1 0098025
Special Requirement 2
Special Requirement 3
Special Requirement 4

Order Comments

Total Weight (lbs)

17,063

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information

Price Level: January 1, 2024

100% Complete

Date: January 02, 2025

Deal: Highway DC

Quote Number: QUO-1073684-P5R8M6

Printed On: 1/8/2025 12:45:33 PM



December 9, 2024

**Customer: CIT
Name: DOUG
T-800 2025
DUPAGE COUNTY**

Prepared By:

Ernie Szabo
GPM Truck Center
4712 Reiland Dr.
Crystal Lake IL 60014
Phone: 224-209-7154

**WET KIT
2 LINE SYSTEM**

INSTALL HOT SHIFT PTO -RDS 4000
DIRECT MOUNT PUMP C-102 WITH AIR SHIFT
INSTALL TOWER CONTROL FOR DUMP AND TAILGATE RELEASE
USE SUPPLIED RIGHT SIDE FUEL TANK FOR HYDRAULIC OIL
INSTALL FITTINGS IN SUPPLIED TANK
INSTALL RETURN LINE FILTER
PROVIDE 50 GAL PREMIUMS HYDRAULIC OIL
1" MALE AND FEMALE WING-COUPLING MOUNTED ON WET PLATE
PLASTIC HALF FENDERS
STEEL REAR MOUNTED CRASH PLATE ADD \$ 1,480.00
INSTALL ELECTRIC TARP SWITCH CAB MOUNTED WITH REVERSING
SOLENOIDS
PROVIDE AND INSTALL ALUMINUM CAB RACK INCLUDES
BAR WINDOW, TWO CHAIN HANGERS AND TWO WORK LIGHTS
WIRED TO THE DASH

\$14,112.00